# **INTERNATIONAL CUSTOM BUILT HOMES, INC.**

6500 CHAPMANS ROAD, ALLENTOWN, PA 18106 PHONE (610) 395-2600 FAX (610) 395-4045

# GENERAL SPECIFICATIONSFOR MOST MODELS\* ONE STORY HOMES UNDER 2,200 SQ. FT.

MORTGAGE ASSISTANCE CUSTOMIZED HOME BLUEPRINTS HOME PLACEMENT ON PROPERTY COMPLETE PERMIT APPLICATION FORMS

## FOUNDATION

Strip topsoil Excavation and backfill 9" x 18" poured concrete footings 10" poured concrete walls, 7'11" high, 3000 PSI Support beam, 8" x 18# steel I beam, steel support columns 4" Concrete floor, 3000 PSI, over 4" crushed stone Coating for damp proofing; sump pit in basement floor Front precast concrete stoop or porch Bilco door to basement Radon pipe under basement floor

## **EXTERIOR WALL CONSTRUCTION**

S-dried, No. 2 and better hem-fir, 2" x 6" studs, 16" O.C. OSB sheathing on home and garage Brick, stone, dryvit or stucco front, per plan, vinyl siding on other 3 sides

#### INSULATION

R 19-21 fiberglass batt in exterior walls R 30-38 blown fiberglass insulation in ceiling R 19 fiberglass batts in basement ceiling

# ROOF

2" x 10", 2" x 8", 2" x 6" kiln-dried, No. 2 and better hem-fir rafters, 16" O.C. 1/2" CDX fir plywood 15 lb felt paper Self seal 30 year architectural fiberglass shingles Aluminum soffit and fascia Seamless aluminum gutters and downspouts

## **INTERIOR WALLS**

2" x 4" S-dried studs, 16" O.C., 8 ft., 9 ft., 10 ft. ceiling height – 1<sup>st</sup> floor 1/2" drywall, glued, nailed, screwed, taped, spackled, sanded and painted

#### **DOORS AND WINDOWS**

Andersen D/H vinyl clad, tilt, High Performance, Low E with screens, and grilles per plan 3 ft 1 3/4" steel insulated front door with 2 sidelights 6 ft. gliding patio door or 6 ft. metal French patio door in rear on most models

#### FLOORING

2" x 10", 2' x 12", S-dried joists, No. 2 and better hem-fir, 16" O.C., with wood bridging 3/4" tongue and groove sheathing grade sub floor, glued and nailed 3/8" plywood underlayment at vinyl areas, Ditra or hardibacker at ceramic tile areas Wall to wall carpet over padding Ceramic tile: Baths and foyer

#### INTERIOR TRIM AND DOORS

Six (6) panel masonite doors with colonial trim throughout Yellow pine stairs to basement

## **ELECTRICAL WIRING**

200 AMP service Trane heat pump with central air Outlets and switches, GFI circuits, and smoke detectors according to electrical code Generous lighting fixture allowance for each home Front door bell and chimes 2 Exterior weatherproof receptacles 5 Phone jacks and 5 TV jacks (6) Recessed lights in kitchen

# PLUMBING

PEX supply lines PVC drain and vent lines 52 gallon high efficiency hot water heater 2 exterior frost-proof water faucets

## BATHROOMS

Main Bath: One piece fiberglass tub with shower Master Bath: One piece fiberglass shower stall with glass door Kohler or Aker bathroom fixtures Moen faucets One piece cultured marble vanity top Ceiling fans vented to exterior

#### **KITCHENS**

Custom built birch or oak cabinets Formica countertop and backsplash General Electric self-cleaning range, potscrubber dishwasher and vented hood One piece no-wax vinyl floor Recessed lights over countertops

## **FINISH WORK**

All hardware for doors, windows, etc. Clothes closets: wire shelf and rod Pantry Closet: all wire shelves Full width mirrors over vanities All bathroom towel bars, accessories, etc.

\* All photos and floor plans were custom built for buyers, thus features and pictures as illustrated may vary from standard.